

MODEL H3274 1/4" Impact Screwdriver INSTRUCTION SHEET





Figure 1. Model H3274.

Introduction

Heavy-duty pneumatic screwdriver features paddle switch for multiple positioning arrangements, forward and reverse switch, pressure clutch and quick-change collet that accepts 1/4" hex screwdriver bits. It has a free speed of 9500 RPM and a torque range of 1.67 to 5 ft/lbs.

| Α. | Impact Screwdriver | 1 |
|----|-----------------------|---|
| B. | Hanger | 1 |
| C. | 1/4" MNPT Air Fitting | 1 |
| D. | Driver Bit | 1 |

Operation

Attach the hanger into the two recesess on the air inlet nut (optional). Insert your driver bit into the collet. The retaining clip will hold it in place. Choose left or right rotation with the directional switch. Control the air pressure with the air pressure dial. Have your inlet pressure set at no more than 80 PSI.

Impact Screwdriver MUST have 3-4 drops of oil directly dropped into the air fitting before each use as shown in **Figure 2**.





Figure 2. Lubricating directly into air fitting.

If you need help with your new pneumatic tool, call our Tech Support at: (570) 546-9663.

H3274 Parts Breakdown and List



| REF | PART # | DESCRIPTION |
|-----|-----------|--------------------|
| 1 | PH3274001 | DRIVER BIT |
| 2 | PH3274002 | RETAINING CLIP |
| 3 | PH3274003 | COLLET |
| 4 | PH3274004 | COMPRESSION SPRING |
| 5 | PH3274005 | NOSE HOUSING |
| 6 | PH3274006 | SHEILD RING |
| 7 | PH3274007 | BUSHING |
| 8 | PH3274008 | STEEL BALL |
| 9 | PH3274009 | MANDREL |
| 10 | PH3274010 | BUSHING |
| 11 | PH3274011 | BEARING |
| 12 | PH3274012 | BOLT |
| 13 | PH3274013 | HAMMER BLOCK |
| 14 | PH3274014 | HAMMER CASE |
| 15 | PH3274015 | SHEILD RING |
| 16 | PH3274016 | TIGHTENING SCREW |
| 17 | PH3274017 | CUSHION |
| 18 | PH3274018 | FRONT COVER |

| REF | PART# | DESCRIPTION |
|-----|-----------|-----------------------|
| 19 | PH3274019 | BEARING |
| 20 | PH3274020 | ROTOR |
| 21 | PH3274021 | CYLINDER |
| 22 | PH3274022 | REAR COVER |
| 23 | PH3274023 | SHEILD RING |
| 24 | PH3274024 | MAIN HOUSING |
| 25 | PH3274025 | COMPRESSION SPRING |
| 26 | PH3274026 | DIRECTIONAL SWITCH |
| 27 | PH3274027 | TRIGGER |
| 28 | PH3274028 | TRIGGER PIN |
| 29 | PH3274029 | HOLE COVER |
| 30 | PH3274030 | PIN |
| 31 | PH3274031 | BOLT |
| 32 | PH3274032 | SCREW |
| 33 | PH3274033 | AIRFLOW DIAL |
| 34 | PH3274034 | AIR INLET NUT |
| 35 | PH3274035 | HANGER |
| 36 | PH3274036 | 1/4" MNPT AIR FITTING |